

Product name VEGAPOINT 24
 Model code P24.XXXXAFMIB
 Order number CP - 222 3PF

Quantity 1
 Production period (days) 6

Compact capacitive limit switch

Application area

VEGAPOINT 24 is designed for level detection of very adhesive products and can reliably detect the coverage state even with the strongest buildup due to the intelligent evaluation. The absolutely front-flush design ensures cleaning without spray shadows.

Your benefit

- Price favourable limit switch with smallest installation dimensions
- Easy integration into control systems through IO-Link communication
- Highly visible coloured 360° status display, adjustable
- Convenient wireless commissioning and diagnostics with smartphone

Explosion protection	XX	without, for Ex-free area (CE, UKCA, RCM, c-CSA-us; in preparation EAC)
Approved as overfill protection	X	without
Foodstuff/Pharmaceutical certificate	X	without
Process fitting / Material	AF	Thread G1 PN25; ISO228-1; hygienic design /316L (Ra<0.76µm); EPDM; universal adapter with O-ring
Electrical connection / Protection	M	M12x1 / IP66/IP67/IP69
Electronics	I	Three-wire transistor (including IO-Link)
Customer-specific adjustment		No
Sensor setting via smartphone and VEGA Tools app	B	with
Additional cleaning procedures		without
Certificate / Standard		without
Measurement loop identification (TAG)		without
Min. process pressure in bar		-1
Max. process pressure in bar		25
Customs tariff number (HS code)		90318080
Software version		Current version